



SX350/SX350S



SX 200/SX220



SX300/SX300S



SX400/SX400S



GRAVIOX 300



GRAVIOX 350

Ref.	Tension	Power	Cutting Capacity	Blade Dimensions
SX200	TRI 400v 50Hz	1 CV (0.75Kw)	L190xH245mm	1640 x 16mm
SX220	TRI 400v 50Hz	1.5 CV (1.1Kw)	L200xH230mm	1740 x 16mm
SX300	TRI 400v 50Hz	2 CV (1.5Kw)	L240xH300mm	2170 x 16mm
SX350	TRI 400v 50Hz	2.5 CV (1.84Kw)	L300xH340mm	2490 x 16mm
SX400	TRI 400v 50Hz	4 CV (3Kw)	L419xH380mm	3150 x 16mm



PM7/PM13 Manuel



PH13/PHX15/PHX25



**TX 98
COMPACT**



82 Classic



TX 98



TX 130 Auto



CRISTAL(Refrigerated)



RUBIS(Refrigerated)

Ref.	Tension	Power	Capacity	Hopper Capacity
TX 98 Compact	TRI 400v 50Hz	4.5 CV (3.3Kw)	950 Kg/h	50 L
82 Classic	TRI 400v 50Hz	1.5 CV (1.1Kw)	300 Kg/h	3 L
TX 98	TRI 400v 50Hz	3 CV (2.2Kw)	500 Kg/h	15 L
TX 130 Auto	TRI 400v 50Hz	10 CV (7.5Kw)	1600 Kg/h	145 L
Cristal	MONO 230v 50Hz	1.5 CV (1.1Kw)	300 Kg/h	4 L
Rubis	TRI 400v 50Hz	1.5 CV (1.1Kw)	300 Kg/h	3.5 L



D300(Vacuum Machine)



D400(Vacuum Machine)



KT-S Fish Scaler