

RLS1315/1330

HANGING LABEL SCALE

Features:

- Fashion appearance
- Support different size receipt paper and label paper
- Waterproof, moisture proof, insect-resistant
- With drawable printer module, convenient operation
- Dual-motor printing module design, more durable
- Unique anti-sloshing patented design



RLS1315/1330 Technical Parameters:

FLASH: extern font 16MB (Master chip: 512KB)

RAM: 8MB

Paper Cutting Tool: sawtooth

Max. Capacity: 15KG/30KG

Min. Capacity: 40g/100g

Verification Scale Interval: 2/5g (6/15g) ; 5/10g (15/30kg)

Accuracy Class: III

DPI(dots per inch): Input Sensitivity: $\geq 50\mu\text{V} / \text{D}$; Zero Adjustment Range: $\pm 60\text{MV}$ Temperature coefficient (range): $\pm 0.0012\%$ CTYP 【Zero】 $\pm (0.2\mu\text{V} + 0.0008\%$ of Dead Load) / $^{\circ}\text{C}$ TYP ; Nonlinearity: 0.01%F.S. ; display resolution: 1/3000 ; A/D ; Conversion rate: 6 times / second

Printing method: Direct thermal printing

Effective Printing Width: 56mm

Paper Width: 30-60mm

Paper Thickness: 0.05-0.5mm

Resolution: 203dpi

Printer Head: 50KM

Printing Speed: 90mm/s

Information / Weight: 5 bytes (APHA value)

Unit Price Digit: 8 digits

Total Price Digit: 8 digits

Weight Unit: g,kg

Display: 79mm * 69mm monochrome LCD screen



Bank



Hospital



Logistics



Postal



Market



Dining



Store



Convenience Store

Danway Emirates LLC

P.O. Box 118446, Dubai, U. A. E. Tel.: +971 4 3473700, Fax : +971 4 3473232
E-mail: info@danwaylrs.com, Toll Free: 800-326929(DANWAY)
Commercial Registry No. 72600 Paid up share capital AED 300,000